

强力粉碎机 Strong Crusher

ISO9001:2000 CE SGS

SML 斯曼尔
www.nb-sml.com
sales@nb-sml.com

强力粉碎机系列 Strong Crusher series

SG-F



静音粉碎机系列 Low Noise Crusher series

SG-J



性能特点 Performance characteristic

强力粉碎机系列

本系列适用于破碎各种软、硬塑胶。包括注塑成型，吹塑成型，及挤压成型后产生的废料。该系列结构紧凑，操作方便。换刀及清洗简便快捷，提高工作效率。

Strong Crusher series

The device is applicable to centralized pulverizing of all kinds of plastics, including the waste of injection moulding, blow molding and extrusion forming. The structure of Crusher is compact for convenient operation, easy cleaning and maintenance which enhances the working efficiency.

注：粉碎最大能力取决于筛网直径。

Note: The crushing capacity depends on the diameter of screen mesh.

规格表: Specifications

型号 Model	粉碎室口径 Chamber Calibre (mm)	破碎能力 Crush Capacity (Kg/H)	动刀片 Rotating Blade (Pcs)	定刀片 Fixed Blade (Pcs)	电机功率 Motor (Kw)	外型尺寸 External Dimensions (L x W x H)	重量 Weight (kg)
SG-230F	200×230	100-150	3×2	2×1	4	920×610×1050	250
SG-300F	200×300	150-200	3×3	2×1	5.5	950×740×1190	400
SG-400F	235×400	200-250	3×4	2×1	7.5	980×840×1300	500
SG-500F	290×500	300-350	3×5	2×2	11	1100×1020×1530	950
SG-600F	320×600	350-450	3×6	2×2	15	1200×1110×1690	1300
SG-800F	540×810	450-600	3×4	2×2	22	2200×1500×2300	2100
SG-1000F	660×1000	600-1000	3×5	2×3	30	2300×1750×2650	2500
SG-1200F	800×1200	800-1200	3×6	2×3	45	2700×2100×3100	3500

性能特点 Performance characteristic

静音粉碎机系列

本系列适用于破碎各种软、硬塑胶。包括注塑成型，吹塑成型，及挤压成型后产生的废料。该系列结构紧凑，操作方便。换刀及清洗简便快捷，提高工作效率。低噪音更是改了工作环境。

Low Noise Crusher series

The device is applicable to centralized pulverizing of all kinds of plastics, including the waste of injection moulding, blow molding and extrusion forming. The structure of Crusher is compact for convenient operation, easy cleaning and maintenance which enhances the working efficiency. Low noise to make the working environment better.

注：粉碎最大能力取决于筛网直径。

Note: The crushing capacity depends on the diameter of screen mesh.

规格表: Specifications

型号 Model	粉碎室口径 Chamber Calibre (mm)	破碎能力 Crush Capacity (Kg/H)	动刀片 Rotating Blade (Pcs)	定刀片 Fixed Blade (Pcs)	电机功率 Motor (Kw)	外型尺寸 External Dimensions (L x W x H)	重量 Weight (kg)
SG-400JV	235×400	100-250	3×2	2×1	7.5	1250×850×1450	950
SG-500JV	290×500	150-300	3×2	2×2	11	1460×970×1660	1300
SG-600JV	320×600	200-350	3×2	2×2	15	1650×1580×1820	1800
SG-800JV	540×810	300-400	3×2	2×2	22	1930×1890×2300	2500